



## Low Loss Flexible Cable L24

### Features:

- \* Ultra-Flexible
- \* Corrosion Resistance
- \* Temperature: -10 °C to 85 °C

### Applications:

- \* Phased-array Radar
- \* Laboratory Test
- \* Small & Complicated Interconnection Occasion

### Technical Specification

| No | Product code | Length (mm) | Frequency (GHz) | Insertion Loss (dB) | Cable diameter (mm) | Connector 1    | Connector 2    |
|----|--------------|-------------|-----------------|---------------------|---------------------|----------------|----------------|
| 1  | L24-PP-110   | 110         | 2.4             | $\leq 1.5$          | $2.8 \pm 0.3$       | SMA PLUG RIGHT | SMA PLUG RIGHT |
| 2  | L24-PJ-80    | 80          | 2.4             | $\leq 1.5$          | $2.8 \pm 0.3$       | SMA PLUG RIGHT | SMA JACK STR   |
| 3  | L24-PJ-130   | 130         | 2.4             | $\leq 1.5$          | $2.8 \pm 0.3$       | SMA PLUG RIGHT | SMA JACK STR   |
| 4  | L24-PJ-190   | 190         | 2.4             | $\leq 1.5$          | $2.8 \pm 0.3$       | SMA PLUG RIGHT | SMA JACK STR   |